

### Applications

- Courier
- Logistic / Transport
- Manufacturing
- Pharmacy
- Retail
- Warehousing



### Packed with features

The CL-E730 table top printer is packed with features usually reserved for higher class machines. Designed and built for easy operation and service, it includes the proven Citizen ARCP™ mechanism, which guarantees sharp, high quality print results.

### Environmentally friendly

Featuring an integrated Energy Star® power supply, the CL-E730 meets today's demand for green IT solutions. With super-low standby power consumption, it is one of the most energy efficient printers available.

### Wii connected

You can also operate the printer remotely and adjust settings thanks to its LinkServer™ management tool which enables you to connect to the printer instantly via a web browser.



The CL-E730 is ideal for tight spaces. Its Hi-Open™ case lifts up vertically, so the printer's footprint doesn't change if the case is open.

# CITIZEN



Featuring on board LAN & USB interfaces, the CL-E730 provides several options for field installation.

## Specifications

Model	CL-E730
Printing Technology	Thermal Transfer + Direct Thermal
Resolution	300 dpi
Print Speed (maximum)	6 inches per second (150 mm/s)
Print Width (maximum)	4 inches (104 mm)
Media Width (min to max)	0.5 - 4.6 inches (12.5 - 118 mm)
Roll Size (max), Core Size	Outside diameter 8 inches (200mm) Core size 1 to 3 inches (25 to 75 mm)
Media Thickness (min to max)	63.5 to 254 µm
Media Length (min to max)	0.25 to 158 inches (6.4 to 4013 mm, depending on emulation)
Media Sensor	Fully adjustable gap, reflective black mark and ribbon near end
Main Interface	Dual Interface USB 2.0 + 10/100 Ethernet (LAN) with LinkServer™
Optional interfaces	Wireless LAN 802.11b and 802.11g standards, 100 metres, 64/128 bit WEP, WPA, up to 54Mbps, Premium Wireless LAN, Ethernet (10/100 BaseT), Serial (RS-232C compliant), Parallel (IEEE 1284 compliant)
Ribbon size	2.9 inches (74mm) maximum outside diameter. 360 metres length. 1 inch (25mm) core
Ribbon winding & type	Ink side in or out, automatically sensing. Wax, Wax/Resin or Resin Type
Ribbon system	ARCP™ automatic ribbon tension adjustment
Mechanism	Hi-Lift™ metal mechanism with wide opening head
Control panel	4 buttons, 2-colour backlit graphic LCD with status LED

Citizen Systems Corporation, 1411 W. 190th Street, Suite 675, Gardena, CA 90248, USA

**Emulations** Cross-Emulation™ - autoswitch between Zebra® and Datamax® emulations

## CL-E730

### Label, Industrial

## Features & Benefits

- Paper load: Front access for all operations including media and ribbon changing
- Printing Speed: Fast print out - 6 inches per second (150 mm per second)
- Display: Backlight LCD control panel for easy configuration
- Hi-Open™ case for vertical opening, no increase in footprint and safe closing.
- No more unreadable labels - the ARCP™ ribbon control technology assures clear prints.
- ENERGY STAR® compliant
- Basic peeler
- USB and Serial cables



With standard operations accessible from the front, this printer is designed for easy loading of media and simple maintenance operation.

CITIZEN SYSTEMS CORPORATION

# CITIZEN

CL-E730

Label, Industrial

<b>Model</b>	<b>CL-E730</b>
<b>Flash (Non-Volatile Memory)</b>	16 MB total, 4MB available for user
<b>Size (W x D x H) and Weight</b>	250 x 458 x 261 mm, 11 Kg
<b>Cutter</b>	Guillotine type, Dealer Installable
<b>Warranty</b>	2 years on printer. 6 months or 50 Kms printhead
<b>EMC and safety standards</b>	CE, TUV, UL

All product names are trademarks of the respective manufacturers. Zebra®, ZPL and EPL are trademarks of ZIH Corp. Datamax® is a trademark of Datamax-O'Neil Corporation. Designs, specifications and availability are subject to change without notice. Errors and omissions excluded. © Citizen Systems Europe GmbH, V.1.0